



US007323667B2

(12) **United States Patent**
Dooley

(10) **Patent No.:** **US 7,323,667 B2**
(45) **Date of Patent:** **Jan. 29, 2008**

(54) **CURIE TEMPERATURE THERMOSTAT FOR A EDDY CURRENT HEATING DEVICE AND METHOD**

(75) Inventor: **Kevin Allan Dooley**, Mississauga (CA)

(73) Assignee: **Pratt & Whitney Canada Corp.**,
Longueuil, Québec (CA)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/082,951**

(22) Filed: **Mar. 18, 2005**

(65) **Prior Publication Data**

US 2006/0219706 A1 Oct. 5, 2006

(51) **Int. Cl.**
H05B 6/10 (2006.01)
H05B 6/06 (2006.01)

(52) **U.S. Cl.** **219/630**; 219/631; 219/667;
219/670

(58) **Field of Classification Search** 219/628–631,
219/634–635, 660–670, 649
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,547,934 A	4/1951	Gill	
2,701,092 A	2/1955	Henshaw	
3,272,956 A *	9/1966	Baermann	219/645
3,445,616 A *	5/1969	Guyer	219/628
3,790,735 A *	2/1974	Peters, Jr.	219/622
3,812,441 A	5/1974	Sakamoto et al.	
3,895,328 A	7/1975	Kato et al.	
3,903,492 A	9/1975	Endo et al.	
4,039,794 A *	8/1977	Kasper	219/618

4,411,715 A	10/1983	Briskin et al.	
4,482,293 A	11/1984	Perry	
4,486,638 A	12/1984	de Bennetot	
4,769,519 A *	9/1988	Hall	219/667
4,896,756 A	1/1990	Matsushita	
4,897,518 A	1/1990	Mucha et al.	
5,397,948 A	3/1995	Zoerner et al.	
5,508,496 A *	4/1996	Hansen et al.	219/633
5,558,495 A	9/1996	Parker et al.	
5,742,106 A	4/1998	Muraji	
5,746,580 A	5/1998	Parker et al.	
5,793,137 A	8/1998	Smith	
5,801,359 A	9/1998	Mano et al.	
5,907,202 A	5/1999	Muraji	
6,180,928 B1	1/2001	Garrigus	
6,232,585 B1 *	5/2001	Clothier et al.	219/620
6,250,875 B1	6/2001	Bauer et al.	
6,296,441 B1	10/2001	Gozdawa	
6,313,560 B1	11/2001	Dooley	
6,503,056 B2	1/2003	Eccles et al.	
6,543,992 B2	4/2003	Webster	
6,607,354 B1	8/2003	Klapatch et al.	

(Continued)

FOREIGN PATENT DOCUMENTS

DE 4226291 * 2/1994


(Continued)

Primary Examiner—Philip H. Leung
(74) *Attorney, Agent, or Firm*—Ogilvy Renault LLP

(57) **ABSTRACT**

The device and method are used for controlling eddy currents generated by an electro-magnetic heater having at least one magnetic field producing element. To control the heater, a source of heat is used to heat a Curie temperature material, located adjacent to the magnetic field producing element. This prevents heat from being generated in the object being heated.

3 Claims, 2 Drawing Sheets



US 7,323,667 B2

Page 2

U.S. PATENT DOCUMENTS

6,630,650	B2	10/2003	Bassill et al.	
6,664,705	B2	12/2003	Dooley	
2003/0102304	A1*	6/2003	Boyers	219/628
2004/0060927	A1*	4/2004	Kim et al.	219/624
2004/0089435	A1*	5/2004	Wang	164/113

FOREIGN PATENT DOCUMENTS

EP	0 836 007	A1	4/1998
JP	61-75897	*	4/1986

* cited by examiner






FIG. 1



1

CURIE TEMPERATURE THERMOSTAT FOR A EDDY CURRENT HEATING DEVICE AND METHOD

TECHNICAL FIELD

The technical field of the invention relates generally to a Curie temperature thermostat and a method for controlling eddy currents used for heating.

BACKGROUND OF THE ART

Eddy currents heaters are used as a source of heat in some devices. However, most of these electromagnetic heaters include permanent magnets for generating the magnetic field that induces the eddy currents. Other heaters may use electromagnets that cannot be controlled from the exterior. As a result, it is thus not possible to control the heat generation without moving the magnets away from the conductive surface in which eddy currents are created, or change the speed at which the magnetic field is moved.

Overall, it would be highly desirable to control the electromagnetic heaters so as to shut off or reduce their heat generation capacity when, for instance, the part being heated reaches its optimum or maximum temperature. Known solutions are restrictive in terms of flexibility of design, since only a few materials have Curie temperatures and so the designer has been limited with existing designs. Room for improvement is available.

SUMMARY OF THE INVENTION

An electromagnetic heater can be controlled when the magnetic field is conducted through a material having a Curie temperature. As a result, the magnetic field can be interrupted or lowered whenever the Curie temperature material is heated at or above its Curie point.

In one aspect, the present invention provides a device for controlling an eddy current heater, the heater comprising at least one magnetic field producing element, the device comprising: a Curie temperature material located adjacent to the magnetic field producing element; and a source of heat to selectively heat the Curie temperature material above the Curie temperature.

In a second aspect, the present invention provides a device for controlling an eddy current heater, the heater comprising at least one magnetic field producing element, the device comprising: an electromagnetically conductive material located adjacent to the magnetic field producing element, the material having a Curie temperature; and means for heating the material above its Curie temperature.

In a third aspect, the present invention provides a method for controlling a heat generation by an eddy current heater used for heating an object, the method comprising: operating the heater to generate heat in the object; determining that the object has received enough heat; and reducing or interrupting the eddy currents generated by the heater by heating a Curie temperature material above the Curie temperature thereof.

Further details of these and other aspects of the present invention will be apparent from the detailed description and figures included below.

DESCRIPTION OF THE DRAWINGS

Reference is now made to the accompanying figures depicting aspects of the present invention, in which:

2

FIG. 1 is a cut-away perspective view of an example rotor with an eddy current heater in accordance with a preferred embodiment of the present invention;

FIG. 2 is a radial cross-sectional view of the rotor and the heater shown in FIG. 1; and

FIG. 3 is an exploded view of the heater shown in FIGS. 1 and 2.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIG. 1 semi-schematically shows an example of a rotating body or rotor **20**, for example an impeller used in a compressor. The rotor **20** comprises a central section, which is generally identified with the reference numeral **22**, and an outer section, which outer section is generally identified with the reference numeral **24**. The outer section **24** supports a plurality of impeller blades **26**. These blades **26** are used for compressing air when the rotor **20** rotates at a high rotation speed. The rotor **20** is mounted for rotation using a main shaft (not shown). In the illustrated example shown in FIGS. 1 to 3, the main shaft includes an interior cavity in which a second shaft, referred to as the inner shaft **30**, is coaxially mounted. This configuration is typically used in multi-shaft gas turbine engines. Both shafts rotate at different rotation speeds. The inner shaft **30** extends through a central bore **32** provided in the central section **22** of the rotor **20**. Referring briefly to FIG. 1, it should be noted that one can use a single shaft rotating system in which the magnets **42** are held fixed while the rotor **20** and its shaft rotate. In that case, the "inner shaft **30**" would be a non-rotating part.

Referring again to FIGS. 1 to 3, the device **40** is provided for heating the central section **22** of the rotor **20** using eddy currents. The electrical conductor is preferably provided at the surface of the central bore **32**. The device **40** comprises at least one magnetic field producing element adjacent to the electrical conductive portion, as will now be explained.

FIGS. 1 to 3 show the device **40** being preferably provided with a set of permanent magnets **42**, more preferably four of them, as the magnetic field producing elements. These magnets **42** are made, for instance, of samarium cobalt. They are mounted around a support structure **44**, which is preferably set inside the inner shaft **30**. Ferrite is one possible material for the support structure **44**. The support structure **44** is preferably tubular and the magnets **42** are shaped to fit thereon. The magnets **42** and the support structure **44** are preferably mounted with interference inside the inner shaft **30**. The position of the magnets **42** and the support structure **44** is chosen so that the magnets **42** be as close as possible to the electrical conductive portion of the rotor **20** once assembled.

The magnets are capable of creating a moving magnetic field relative to the object to be heated. In this example, the set of magnets **42** and the support structure **44** are mounted on the inner shaft **30** which generally rotates at a different speed with reference to the outer shaft and rotor **20**. This magnetic field will circulate around a magnetic circuit including the electrical conductor portion in the central section of the rotor **20**, since the inner shaft **30** is made of a magnetically permeable material.

The electrical conductor portion of the central section **22** of the rotor **20** can be the surface of the central bore **32** itself if, for instance, if the rotor **20** is made of a good electrical conductive material. If not, or if the creation of the eddy currents in the material of the rotor **20** is not optimum, a sleeve or cartridge or coating made of a more suitable material can be provided inside the central bore **32**. In the

illustrated embodiment, the device 40 comprises a cartridge made of two sleeves 50, 52. The inner sleeve 50 is preferably made of cooper, or any other very good electrical conductor. The outer sleeve 52, which is preferably made of steel, or any material having similar properties, is provided for holding the inner sleeve 50. The pair of sleeves 50, 52 can be mounted with interference inside the central bore 32 or be otherwise attached thereto.

In use, the rotor 20 of FIG. 1 rotates at a very high speed and air is compressed by the blades 26. This compression generates heat, which is transferred to the blades 26 and then to the outer section 24 of the rotor 20. However, at the same time, relative rotation between the rotor 20 and the magnets inner shaft 30 creates a moving magnetic field in the inner sleeve 50 attached to the rotor 20, thereby inducing eddy currents therein. The material is then heated and the heat is transferred to the outer sleeve 52 and to the outer section 24 itself. In this example, the invention thus helps heat the central bore 32 of the rotor 20.

As aforesaid, ferrite is one possible material for the support structure 44. Ferrite is a material which has a Curie point. The Curie point can be generally defined as the temperature at which there is a transition between the ferromagnetic and paramagnetic phases. When an electromagnetically conductive material having a Curie point is heated above a temperature referred to as the "Curie temperature", it losses its ferromagnetic properties and becomes a magnetic insulator. This feature can be used to control heat generation by the device 20 once the inner section 22 of the rotor 20 reaches the maximum operating temperature, through the selection of a material having a desired Curie temperature. Accordingly, the support structure 44, when made of ferrite or any other material having a Curie point, can be heated to reduce the eddy currents. In this example, heat is produced using a flow of hot air 60 coming from a section of the engine or mechanical system, with which rotor 20 is associated, and this air is directed inside the inner shaft 30. Thus, heat is supplied to the Curie temperature material controllably in sufficient amount to "shut off" the Curie temperature material when it is determined that the object being heated has received enough heat. Temperature sensors and a controlled heat source 62 can be used for that purpose. Control over the heat generation may otherwise be provided using a timer counting the running time of the engine 10, or any other way, including a manual intervention. Alternately, heat generated simply through the normal operation engine or system with which rotor 20 is associated may be used to automatically heat the Curie temperature material. The material composition may be selected to provide an appropriate or advantageous Curie temperature for the Curie temperature material, as well. Still alternately, the invention may be provide in a configuration such that heat from the

object being heated may feedback to the Curie temperature material in order to shut it down. Other possibilities will also be apparent to the skilled reader in light of this description.

The above description is meant to be exemplary only, and one skilled in the art will recognize that changes may be made to the embodiments described without departing from the scope of the invention disclosed. For example, the device can be used with different kinds of rotors than the one illustrated in the appended figures, including turbine rotors. It can also be used in other environments in which relative motion of a magnetic material may be generated, and is not limited to rotating shaft systems, those these are best suited to practising the invention. The rotating system need not be constant speed, not include multiple rotating bodies, nor include shafts, nor be limited to configurations where the magnets rotate or are disposed inside the object to be heated. Any suitable configuration employed the principle taught herein may be used. The Curie temperature material can be set around the magnets or the other magnetic field producing elements. More than one distinct Curie temperature material can be used to obtain different degrees of control. The magnets can be made of a different material than samarium cobalt. The magnets can also be provided in different numbers or with a different configuration than what is shown. The use of electromagnets is also possible. Other materials than ferrite are possible for the Curie temperature material. The heat used to increase the temperature of the Curie temperature material can come from a different source than a source of hot air. For instance, an electrical element can be used for that purpose. Still other modifications which fall within the scope of the present invention will be apparent to those skilled in the art, in light of a review of this disclosure, and such modifications are intended to fall within the appended claims.

What is claimed is:

1. A method for controlling a heat generation by a permanent magnets heater used for heating an object, the method comprising:
 - operating the heater to generate heat in the object;
 - determining that the object has received enough heat; and
 - reducing or interrupting the eddy currents generated by the permanent magnets heater by heating a Curie temperature material above the Curie temperature thereof.
2. The method as defined in claim 1, wherein the Curie temperature material is heated using a source of hot gas.
3. method as defined in claim 2, wherein the Curie temperature material is heated using heat feedback from the object.

* * * * *